

# iX4



Designed to fit your considerable printing needs



## For high volume printing

With new mechanical design, iX4 series supports a large 8.26 inch outer diameter label roll and up to 450 meter ribbon capacity.



## Printing speed upgrade to 8 inches/sec

Featuring 8 ips print speed, even print with the highest speed, it can still maintain the perfect print quality.



## Multiple interfaces

The iX4 series has built-in Ethernet, Dual USB hosts, USB device, RS-232, and it can be expanded with Wi-Fi, GPIO card/Parallel port.


## Applications




Manufacturing



Transportation & Logistics



Distribution



Health Care

Print Specifications	iX4-250	iX4-350
Print Method	Direct Thermal & Thermal Transfer	
Print Resolution	203 dpi (8 dots/mm)	300 dpi (12 dots/mm)
Print Speed (Max.)	8 ips	6 ips
Print Length (Max.)	100"(2540 mm)	50"(1270 mm)
Print Width (Max.)	4.25"(108 mm)	4.16"(105.7 mm)
Onboard Memory	32 MB SDRAM, 16MB Flash ROM (USB storage up to 32GB)	
CPU Type	32 bit RISC microprocessor	

Consumables Specifications	
Sensors	Media Transmissive sensor x 1 (movable) / Media Reflective sensor x 1 (movable) & Head open switch / Ribbon end sensor
Media Type	Roll-feed, die-cut, continuous, fan-fold, tags, ticket in thermal paper or plain paper
Media	Max. width:4.48"(114mm). Min. width: 1" (25.4 mm). Thickness: 0.0025"~0.01" (0.0635mm~0.254mm) 8.26"(210mm) OD on a 3"(76mm) ID core. 7"(177.8mm) OD on a 1.5"(38mm) ID core.
Ribbon	Max. width:4.4"(112mm). Min. width: 1" (25.4 mm). Length:max 450m Wax, Max OD 3.2" (81.3mm). Core size ID 1"(25.4mm). Wax, Wax/Resin, Resin (Ribbon wound ink-side out or ink-side in: auto-detect)

Fonts & Symbologies	
Fonts	Internal character sets standard support. Soft fonts are downloadable
1D code	UPC-A, UPC-E, JAN/EAN, CODE39, CODE93, CODE128, GS1-128 (UCC/EAN128), CODABAR (NW-7), ITF, Industrial 2of5, MSI, UPC add-on code, POSTNET, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Limited, GS1 DataBar Expanded, GS1 DataBar Expanded Stacked
2D code	QR Code, PDF417 (including MicroPDF), DataMatrix (ECC200), GS1 DataMatrix, MaxiCode
Composite Symbol	EAN-13 Composite (CC-A/CC-B), EAN-8 Composite (CC-A/CC-B), UPC-A Composite (CC-A/CC-B), UPC-E Composite (CC-A/CC-B), GS1 DataBar Composite (CC-A/CC-B), GS1 DataBar Truncated Composite (CC-A/CC-B), GS1 DataBar Stacked Composite (CC-A/CC-B), GS1 DataBar Expanded Stacked Composite (CC-A/CC-B), GS1 DataBar Expanded Composite (CC-A/CC-B), GS1 DataBar Stacked Omnidirectional Composite (CC-A/CC-B), GS1 DataBar Limited Composite (CC-A/CC-B), GS1-128 Composite (CC-A/CC-B/CC-C)

Interface Characteristics and Integration	
Operation Interface	Standard: LED indicator x 3, Button x 3, Multiling Back-lit LCD Display 16 x 2-line & RTC Factory Option: Buzzer
Communication Interface	Standard: Ethernet, Dual USB hosts, USB device, RS-232 Dealer Option: Wi-Fi (IEEE 802.11 b/g/n), GPIO card/Parallel port
Programming Language	PPLA+PPLB+PPLZ
Graphics	<u>PPLA</u> : PCX, BMP, IMG, HEX,GDI <u>PPLB</u> : PCX, BMP, Binary raster, GDI <u>PPLZ</u> : GRF, Hex, GDI
Software-Label Editing	Windows Driver (Windows XP/Vista/Win7/Win8/Win10), BarTender® from Seagull Scientific
Software-Utility	Printer Tool
Optional Accessory	Guillotine-Full Cutter / Partial Cutter, Rotary Cutter, Peeler, External media stand

Operating & Environment Characteristics	
Power Source	Internal Universal Switching Power supply. Input voltage: 100~240V, 50~60Hz
Operation Environment	Operation Temperature: 40°F~100°F (4°C~38°C). 10%~90% non-condensing. Storage Temperature: -4°F~122°F (-20°C~50°C)
Agency Listing	CE, CB, UL/cULus, FCC, ICES, Energy Star

Physical Characteristics	
Dimensions	W 250 mm x H 263 mm x D 418 mm
Weight	24 lbs (11 kg)

\*This data sheet is for informational purpose only. Argox makes no warranties, expressed or implied in this summary. Specifications are subject to change without notice. All trade marks are the property of their respective owners. For more specific information, please refer to owner's manual.

